

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 05-017705
 (43)Date of publication of application : 26.01.1993

(51)Int.Cl. C09C 3/12
 C08K 9/06
 C08L 21/00

(21)Application number : 03-020872 (71)Applicant : DEGUSSA AG
 (22)Date of filing : 14.02.1991 (72)Inventor : WOLFF SIEGFRIED
 GOERL UDO
 DEUSSER HANS

(30)Priority
 Priority number : 90 4004781 Priority date : 16.02.1990 Priority country : DE

(54) METHOD FOR MODIFYING SURFACE OF FILLER, MODIFIED FILLER AND VULCANIZABLE RUBBER COMPOSITION

(57)Abstract:

PURPOSE: To obtain fillers with storage stability by a method wherein surface modification of oxide or silicate fillers is performed by a two-stage process using specified organosilicone compounds.

CONSTITUTION: A natural or synthetic, oxide or silicate filler (A) is intensively mixed with an organosilicon compd. (B) of formula [wherein B is -SCN (when q=1) or -Sx (when q=2); R and R1 are

each a 1-4C alkyl, a phenyl, etc.; n is 0, 1 or 2; $\left[\sum_{i=1}^n (RC)_j - n \text{ Si} - (A)_m - (Ar)_p \right]_n [D]$

Alk is a 1-6C divalent hydrocarbon; m is 0 or 1;

Ar is a 6-12C arylene; p is 0 or 1; x is 2-8] at a

temp. of 60°C or lower under a concn. of 3.5×10^{-6}

mol or lower trialkoxysilyl group per 1 m² surface

of the ingredient A. Then, hydrophobing reaction

of the homogenized mixture is performed in a

preheated mixer in a reactor such as heat treating

floor at 60°C or higher.

LEGAL STATUS

[Date of request for examination] 02.07.1996

[Date of sending the examiner's decision of rejection] 18.05.1999

[Kind of final disposal of application other than the examiner's decision of

rejection or application converted
registration]

[Date of final disposal for application]

[Patent number] 3019167

[Date of registration] 07.01.2000

[Number of appeal against examiner's
decision of rejection] 11-13131

[Date of requesting appeal against
examiner's decision of rejection] 16.08.1999

[Date of extinction of right]